

TECHNICAL SPECIFICATIONS

B SERIES



Distributed by Digizoo

70''

Panel	Optimum Resolution	Ultra HD 3840x2160@60Hz
	Back Light Unit	E-LED
	Response Time	6ms (Typical)
	Viewing Angle (Horizontal/Vertical)	176° / 176°
	Contrast Ratio	4000 : 1 (Typical)
	Brightness	300 cd/m² (Typical)

Touch	Touch Technology	Projected Capacitive (PCAP)
	Simultaneous Touch Points	50
	Touch Accuracy	1mm (Max)
	Response Time	30ms (Max)
	Touch Compatibility Supported OS (Multi)	Windows 7/ 8 / 8.1 / 10, Android 4.3 ~, Linux kernel 3.8~

Features	Dual OS Support	Yes
	Windows Support	Yes (Via OPS)
	Android Support	Yes (Built-In)
	4PIP	Yes
	Home Button	Yes
	Touch OSD	Yes
	Direct Bonding	Yes

Internal Android	Chipset	RK3288
	Core	Cortex A17 Quad Core
	GPU	Mali T764
	OS Version	KitKat 4.4.2
	RAM/Storage	2GB/16GB

Glass	Anti-Glare	Yes
	Shatter Resistant	Yes
	Thickness	1.8mm (Chemical Strengthened)

70"

Connectivity

HDMI 2.0	1
HDMI (MHL)	1
HDMI	1
Display Port 1.2	1
Touch Sensor USB	1
USB Update	1
USB 2.0	1
USB 3.0	1
Gigabit WAN	1
Gigabit LAN	1
VGA Input	1
Video Component	-
A/V	-
Sound Bar Input	-

Mechanical

Outline Dimensions	1608.0mm x 936.0mm x 97.0mm
Packaged Outline Dimensions	1820.0mm x 1115.0mm x 300.0mm
Product Weight	62.3kg
Gross Weight	74.3kg
Installation Type	Stand, Wall Mount
Mount Type	VESA 400(H) x 400(V)
Power Input Range	100V~240V~
Viewing Orientation	Landscape Only
Regulatory Approval	CE, RoHS Green Compliant
Manufacture's Warranty	2 Years


Environmental

Operating Temperature	0°C~40°C
Storage Temperature	-10°C~60°C
Operating Humidity	20%~80%
Storage Humidity	10%~90%


Accessories



AC Power Cable




HDMI Cable



Remote Control



Touch Sensor USB Cable



D3 Quick Manual

TECHNICAL DRAWINGS

B SERIES

Front View

Rear View

